

FD50 FD60 FD70 Wide view mast VM

Mast Model	Load center 600mm			Max. lift height	Mast height		Free lift with backrest			Tilt angle fwd-bwd	Weight with backrest		
	FD50	FD60	FD70		fork lowered	fork lift with backrest	FD50	FD60	FD70		FD50	FD60	FD70
	kg	kg	kg		mm	mm	mm	mm	mm		mm	mm	mm
VM300	5000	6000	7000	3000	2500	4420	205	205	210	6 - 12	8050	8750	9450
VM330	5000	6000	7000	3300	2650	4720	205	205	210	6 - 12	8100	8800	9500
VM350	5000	6000	7000	3500	2750	4920	205	205	210	6 - 12	8130	8830	9530
VM400	5000	6000	7000	4000	3050	5420	205	205	210	6 - 12	8320	9020	9720
VM450	5000	6000	7000	4500	3300	5920	205	205	210	6 - 12	8410	9110	9810
VM500	5000	6000	7000	5000	3550	6420	205	205	210	6 - 6	8520	9220	9920
VM550	4750	5700	6600	5500	3850	6920	205	205	210	3 - 6	8720	9420	10120
VM600	4400	5400	6400	6000	4100	7420	205	205	210	3 - 6	8800	9500	10200

FD50 FD60 FD70 2 Stage free lift mast VFM

Mast Model	Load center 600mm			Max. lift height	Mast height		Free lift with backrest			Tilt angle fwd-bwd	Weight with backrest		
	FD50	FD60	FD70		fork lowered	fork lift with backrest	FD50	FD60	FD70		FD50	FD60	FD70
	kg	kg	kg		mm	mm	mm	mm	mm		mm	mm	mm
VFM210	5000	6000	7000	2100	2175	3520	555	555	555	6 - 12	7881	8581	9281
VFM300	5000	6000	7000	3000	2625	4420	1255	1255	1260	6 - 12	8110	8810	9510
VFM330	5000	6000	7000	3300	2775	4720	1405	1405	1410	6 - 12	8160	8860	9560
VFM350	5000	6000	7000	3500	2875	4920	1505	1505	1510	6 - 12	8190	8890	9590
VFM400	5000	6000	7000	4000	3175	5420	1805	1805	1810	6 - 12	8390	9090	9790

FD50 FD60 FD70 3 Stage free lift mast VFHM

Mast Model	Load center 600mm			Max. lift height	Mast height		Free lift with backrest			Tilt angle fwd-bwd	Weight with backrest		
	FD50	FD60	FD70		fork lowered	fork lift with backrest	FD50	FD60	FD70		FD50	FD60	FD70
	kg	kg	kg		mm	mm	mm	mm	mm		mm	mm	mm
VFHM400	4500	5500	6200	4000	2500	5400	1130	1130	1135	6 - 10	8640	9340	10040
VFHM435	4500	5500	6200	4350	2650	5750	1255	1255	1260	6 - 10	8720	9420	10120
VFHM480	4500	5500	6200	4800	2775	6200	1405	1405	1410	6 - 10	8800	9500	10200
VFHM500	4500	5500	6200	5000	2875	6400	1505	1505	1510	6 - 10	8860	9560	10260
VFHM600	4200	5000	5500	6000	3300	7400	1930	1930	1935	3 - 6	9220	9920	10620

FD80 FD100 Wide view mast

Mast Model	Load center 600mm		Max. lift height	Mast height (FD100)		Free lift with backrest	Tilt angle fwd-bwd	Weight with backrest	
	FD80	FD100		(1) fork lowered	(2) fork lift with backrest			FD80	FD100
	kg	kg		mm	mm			mm	mm
VM300	8000	10000	3000	2850	4330	205	6 - 12	10450	12450
VM350	8000	10000	3500	3100	4830	205	6 - 12	10560	12560
VM400	8000	10000	4000	3400	5330	205	6 - 12	10810	12810
VM450	8000	10000	4500	3650	5830	205	6 - 12	10920	12920
VM500	7800	10000	5000	3900	6330	205	6 - 6	11020	13020
VM550	7400	9000	5500	4200	6830	205	3 - 6	11270	13270
VM600	7000	8000	6000	4450	7330	205	3 - 6	11380	13380

Notes:
 (1) Fork lowered for FD80:-225mm;
 (2) Fork lift with backrest for FD80:+90mm;

KBZ'S products and its specifications change without prior notice



Distributor

Folangsi Machine Co., Ltd.

Tel: +86 020-3999 3595 Fax: +86 020-3999 3597

E-mail: admin@folangsiforklift.com

Address: No.13 Bangyan Road,
 Panyu District, Guangzhou, China



FD Series 50-100 Counter Balanced Forklift



Three Features



1 New style environmental protection and efficient engine.

Equipped with powerful and efficient engine, suitable for the latest Chinese II emission standard and Europe III emission standard(S6ST).

2 Hydraulic steering system

Steering system with horizontal cylinder provides with fixable and convenient veer operation and maintainability.



3 Wide view mast

Preeminent front operation view with unique designed wide view mast (model VM), makes safer and more reliable operation.

